

PolySpun 300

PolySpun 300 is constructed from polyester fibers spunbond into a swirling web pattern. PolySpun 300 has exceptional strength to weight ratio. The natural qualities of polyester provide exceptional ultraviolet stability. PolySpun 300 has unequalled water and air permeability.

Applications:

- Landscape / weed control
- Patio / sidewalk underlying
- Drainage / septic line wrap
- Soil separator

Benefits:

- Exceptional toughness and strength
- More economical and less bulky than woven
- Easy to cut and handle
- Superior weed control
- Excellent water and air permeability

Fabric Properties

Basic Weight

Thickness

Grab Tensile

Grab Elongation

Trapezoidal Tear Strength

Water Flow Rate

Permittivity

Apparent Opening Size

Puncture Strength

Burst Strength

UV Degradation

PolySpun 300

3.0 oz/sq. yd.

21.0 mils

79/74 lbs.

52/56 %

35.5/39 lbs.

275 gallons/min./sq. ft.

2.09 sec/penetration

60/0.25 US Std. Sieve

45.1 lbs.

122 psi

75% of fabric retained
(150 hrs.)

Sizes:

3' x 300'

4' x 300'

5' x 300'

6' x 100'

6' x 300'

7' x 300'

8' x 300'

9' x 300'

12' x 300'

16' x 300'

